

110° 3D adjustable hinges, soft close

Integrated soft closing mechanism with mounting plate.

Full or half overlay mounting.

Full overlay




Half overlay



Description


Material:	Steel cup & hinge arm
Diameter of hinge cup:	35 mm
Depth of hinge cup:	11.5 mm
Door thickness:	14-22 mm
Drilling pattern:	48 / 6
Adjustment facility:	Side ± 1.5 mm Height ± 2 mm (via mounting plate) Depth from -1 to +3 mm

Full overlay mounting



Door overlay mm				
14.5	15.5	16.5	17.5	
3	4	5	6	0
Distance to cup E mm			Mounting plate distance mm	

Half overlay mounting




Door overlay mm				
7.5	8.5	9.5	10.5	
3	4	5	6	0
Distance to cup E mm			Mounting plate distance mm	



Height adjustment ± 2 mm via eccentric




For chipboard screws*



With Euro screws



Hinge Plates



Item ID No.

110° Clip-on Hinges	Cat. No.
Nickel Plated (Full overlay with soft close)	BG-320.01.050
Nickel Plated (Half overlay with soft close)	BG-320.01.051

Item ID No.

4 Hole Hinge Plate*	BG-323.01.050
Hinge Plate for Aluminium Doors**	BG-324.01.050