

Product details	CE/DoP Code	EN 14041	WVH2001
	Usage Classification	EN NF ISO 10874	33 / 42
	Manufacturing Standard	EN ISO 10582	Conform
	Dimensions	EN ISO 24342	308 x 600 mm
	Total Thickness	EN ISO 24346	5 mm
	Core Thickness	EN ISO 24346 2,218	3,45 mm
	Wear Layer Thickness	EN ISO 24340	0,55 mm
	Weight / m ²	EN ISO 23997	8200 g/m ²
	Density		2,1 kg/m ³
	Underlay Type		IXPE
	Planks / Box		12
	Area / Box		2,218
	Box / Pallet		66
	m ² / Box		146.36
Technical properties	Abrasion Resistance	EN 13329 - Annex 3	> 2000 cycles
	Abrasion	EN 660-2	T Group
	Residual Indentation	EN ISO 24343-1	≤ 0,15 mm
	Dimensional Stability to Heat	EN ISO 23999	Long. 0.08% / width. 0,02%
	Curling to Heat	EN ISO 23999	≤ 1,0 mm
	Slip Restraint	DIN 51130	R10
		EN 13893	DS : > 0,37
	Chemical Resistance	EN ISO 26987	Class 0
	Colour Fastness to Light	EN ISO 105-B02	≥ 6
	Flammability / Smoke Emissions	EN 13501-1	Bfl-S1
	Castor Chair / Resistance (type W)	ISO 4918:2009	Pass
	Impact Sound Insulation ΔLw	ISO 712-2	18
	Thermal Resistance	EN 12667	0.030 (m ² .K)/W
	Electrostatic Performance	ISO 24334	< 2kV
	Lock Strength	ISO 24334	Long side: > 0.85 kN/m Short side: > 0.85 kN/m
	Underfloor Heating Suitability	EN 12524	Suitable for underfloor heating, max 27°C
Environment	TVOC After 28 Days (AgBB Test)	ISO 16000-9	≤17 ug/m ³
	VOC Emission Class (French Regulations)	ISO 16000-9	A+
	Formaldehyde Group	EN 717-1	E1
	REACH (European Reglementation) Conformity	1907/2006/CE	Conform
	Plasticizer	EN 14372	DOTP - Virgin PVC - 100% ortho-phthalate free
	Recyclability		100%
Warranty	Warranty Residential		25 years
	Warranty Commercial		10 years



SURFACE PROTECTION

Resistant to both scratches and stains. Waterproof and engineered to perfection. Tried and tested. Provides hygienic, durable protection. Easy to clean.

WEAR LAYER

Resistant to everyday wear and tear, this extends the life of the investment.

HIGH DEFINITION FILM

Various patterns offer an extensive collection from which to choose. Undeniable sturdiness underfoot.

RIGID CORE

Our waterproof rigid core technology allows easy installation over imperfect subfloors, elevating resilience and comfort. High dimensional stability.

ACOUSTIC UNDERLAY

Provides better sound absorption and an excellent underfoot feeling.