

Product details	CE/DoP Code	EN 14041	SVH2-01-2019
	Usage Classification	EN ISO 10874	23 / 33
	Production Norm		EN 16511
	Bevel		Beveled 4 sides
	Click Type		I4F
	Total Thickness	EN ISO 24346	5,5 mm
	Core Thickness	EN ISO 24346	3,95 mm
	Top Layer Thickness	EN ISO 24340	0,55 mm
	Acoustic Underlay		IXPE
	Underlay Thickness		1 mm
	Dimensions	EN ISO 24342	228 x 1520 mm
	Weight / m ²	EN ISO 23997	8960 g/m ²
	Box		2,426 m ²
	Pallet		116.44 m ²
Technical properties	Wear Resistance	EN 13329 - Annex 3	> 4500 cycles
	Residual Indentation	EN ISO 24343-1	< 0,1 mm
	Dimensional Stability	EN ISO 23999	< 0,10 %
	Dimensional Stability	EN ISO 23999	0 mm
	Slip Resistance Wet	DIN 51130	R10
	Stain Resistance	EN 438-2	Group 1, 2 & 3: grade 5
	UV Resistance	EN ISO 105-B02	> 6
	Fire Rating	EN 13501-1	Bfl-S1
	Castor Chair Test	ISO 4918:2009	Compliant (25,000 cycles)
	Room Impact Insulation	ISO 712-2	21 dB
	Thermal Resistance	EN 12667	0,059 m ² K/W
	Lock Strength	ISO 24334	> 4 kN/m
Environment	Floor Heating	EN 12664	Suits floor heating max 27°C
	TVOC After 28 Days (AgBB Test)	ISO 16000-9	< 20 ug/m ³
	VOC Emission Class (French Regulations)	ISO 16000-9	A+
	Formaldehyde Group	EN 717-1	E1
	REACH (European Reglementation) Conformity 1907/2006/CE		Conform
Warranty	Plasticizer	EN 14372	DOTP - Virgin PVC - 100% ortho-phthalate free
	Warranty Residential		25 years
	Warranty Commercial		10 years