

SOLAS 4-way non switchable direct driver. An AC/DC isolated power supply specifically designed for 20W flicker-free downlights and other lamps.



Input

Parameter	Condition	Unit	Min	Average	Max
Voltage	Continuous	V _{ac}	200	230	240
Frequency	V _n = 200-240 V _{ac}	Hz	50	50	50
Power factor	V _n = 200-240 V _{ac} 50/60 Hz V _i = 12 V I _i = 1.67 A		0.4		
Current	V _n = 200 V _{ac} / 60 Hz V _i = 12 V I _i = 1.67 A	mA	260		
Power	V _n = 200-240 V _{ac}	W	25		

Output

Parameter	Condition	Unit	Min	Average	Max
Voltage	V _n = 200-240 V _{ac} 12 V / 1.6 A	V _{dc}	11.4	12	12.6
Current	V _n = 200-240 V _{ac}	mA	1670	1670	1670
Voltage variation	V _n = 200-240 V _{ac}	%	-5%		+5%
Power	V _n = 200-240 V _{ac} I _i = 0 mA	W		<0.3	
Efficiency*	V _n = 230 V 12 V / 1670 mA	%		84	

*Environmental temperature of 25° C

Item ID No.

Finish/Colour	Size (WxDxH) mm	Cat. No.
Black	120 x 55 x 16 mm	BG-871.08.00.04

Safety

Parameter	Condition	Unit	Parameter value
Safety standard			Meet UL, TUV, GS certification requirement

Environmental conditions

Operating temperature range:	-20° C ~ +40° C
Storage temperature range:	-20° C ~ +70° C
Operating humidity:	20 ~ 90%

Life cycle

MTBF:	B10 ≥ 20,000 hr
Electrolytic capacitor:	30,000 hr

