

SOLAS 6-way asynchronous monochrome wireless control box. Programmable individual channels enhancing the customizability of your LED system.



### Wireless features

<b>Frequency:</b>	ISM 2402-2482 MHz
<b>Crystal frequency:</b>	24 MHz
<b>Modulation:</b>	GFSK
<b>Transmit power:</b>	0 dbm
<b>TIS:</b>	-70 dbm
<b>Emission:</b>	16 mA (0 dbm)

### Description

<b>Input voltage:</b>	12/24 V <sub>DC</sub>
<b>Input/Output variation range:</b>	11.4/25.2 V <sub>DC</sub>
<b>Input current:</b>	5 A
<b>PWM frequency:</b>	1 KHz
<b>Minimum brightness:</b>	5% Duty
<b>Soft on/off:</b>	2s +/- 20%
<b>Dimming:</b>	5s +/- 20%
<b>Usage:</b>	Smart Driver 872 required Wireless Sensors 860/861/862/863 required

### Environmental conditions

<b>Operating temperature range:</b>	-10° C ~ +45° C
<b>Storage temperature range:</b>	-20° C ~ +70° C
<b>Operating humidity:</b>	5 ~ 95%

### Item ID No.

Finish/Colour	Size (WxDxH) mm	Cat. No.
Black	50 x 75 x 15 mm	<b>BG-881.08.001.04A</b>

